

MIXER[®]

Technology for
building industry



Stators and Rotors



INDEX

PAGE

THE STANDARD MODELS

04

THE SPECIAL MODELS

13

THE HIGH PRESSURE MODELS

23

THE HIGH OUTPUT MODELS

27



Mixer Technology SRL has been producing **rotors and stators** for the construction industry since 1986. Since then, we have created a wide range of products to satisfy the requirement in term of durability and flow-rate requested by our customers.












Pumps 1, 2, 3, 4, 5 and 6 are adapted to every premixed gypsum based, gypsum-lime based, cement-lime based plasters, floor-screeds, glues and finishing products and can be used with all three-phased machines in the market.

As for single-phased machines, we advise to use the pumps 13, 26, 30 and 32.

Mixer Technology SRL also manufactures a wide range of **building machines** to respond to the different application requirements of the sector: **spraying machines, mixing machines, pneumatic conveying systems** for powder products for mortar.

LEGEND

The different models of rotor head

| | | | | | | | | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |  |  |  |  |
| Slit | Bayonet | Slit and holed | Slit and holed Ø10 | Holed Slit one hole | Holed Slit two hole | Flattened with hole | Squared | Squared and holed | Hexagonal | Hexagon socket |

Type of rotor material:

HR

Special high strength material

C

Steel material for standard performance (not gypsum)

Rotation of mixing shaft:



Direction of mixing shaft rotation

Essential:



Reference (cat. C5)
3M07701000





ANTIGRIP

To facilitate the assembly of every models of rotors

THE STANDARD MODELS





MIXER 1 D6-3 long life



| | BOOSTER STATOR | | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|----------------|-----------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00503200 | 3F00503201 | 3F00502200 | 3F00502203 | Ref. (cat. C4) | 7009049200 | 7009308000 | 7009050100 |
| With anti-rotation | - |  | - |  | With anti-rotation | - |  | - |
| Type | D6-3 long life | | | | Rotor head model |  | | |
| RPM | 400 | | | | | | | |
| Flow-rate (L/min) | 22 | | | | Material used | HR | HR | C |
| Max pressure (bar) | 30 | | | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business</div> | | | |
| Grain size (mm) | 3 | | | | | | | |
| SH = shore | 70 | | | | | | | |
| Stator Ø | 90 | | | | | | | |
| Length (mm) | 270 | | | | | | | |





MIXER 2 D7-2,5



| | BOOSTER STATOR | | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|----------------|-------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00503300 | 3F00503301 | 3F00502300 | 3F00502302 | Ref. (cat. C4) | 7009049400 | 7009309000 | 7009050300 |
| With anti-rotation | - |  | - |  | With anti-rotation | - |  | - |
| Type | D7-2,5 | | | | Rotor head model |  | | |
| RPM | 400 | | | | Material used | HR | HR | C |
| Flow-rate (L/min) | 27 | | | | | | | |
| Max pressure (bar) | 30 | | | | | | | |
| Grain size (mm) | 3 | | | | | | | |
| SH = shore | 70 | | | | | | | |
| Stator Ø | 90 | | | | | | | |
| Length (mm) | 270 | | | | Can be used with the following machines | | | |
| | | | | | Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Koine 3 Imer, Koine 4 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business | | | |




MIXER 3 D8-2



| | BOOSTER STATOR | | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|----------------|-----------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00503400 | 3F00503401 | 3F00501701 | 3F00501703 | Ref. (cat. C4) | 7009029000 | 7009310000 | 7009050400 |
| With anti-rotation | - |  | - |  | With anti-rotation | - |  | - |
| Type | D8-2 | | | | Rotor head model |  | | |
| RPM | 400 | | | | Material used | HR | HR | C |
| Flow-rate (L/min) | 32 | | | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Koine 4 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business</div> | | | |
| Max pressure (bar) | 30 | | | | | | | |
| Grain size (mm) | 3 | | | | | | | |
| SH = shore | 70 | | | | | | | |
| Stator Ø | 90 | | | | | | | |
| Length (mm) | 270 | | | | | | | |

MIXER 4



| | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|-----------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00502400 | 3F00502401 | Ref. (cat. C4) | 7009049500 | 7009305000 | 7009050800 |
| With anti-rotation | - |  | With anti-rotation | - |  | - |
| RPM | 400 | | Rotor head model |  | | |
| Flow-rate (L/min) | 40 | | Material used | HR | HR | C |
| Max pressure (bar) | 25 | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Koine 3 Imer, Koine 4 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business</div> | | | |
| Grain size (mm) | 3 | | | | | |
| SH = shore | 70 | | | | | |
| Stator Ø | 90 | | | | | |
| Length (mm) | 270 | | | | | |




THE STANDARD MODELS

MIXER 5



STRAIGHT STATOR

ROTOR

| Reference (cat. C4) | 3F00502500 | 3F00502501 | Ref. (cat. C4) | 7009049600 | 7009306000 | 7009050900 |
|---------------------|------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|
| With anti-rotation | - |  | With anti-rotation | - |  | - |
| RPM | 400 | | Rotor head model |  | | |
| Flow-rate (L/min) | 50 | | | | | |
| Max pressure (bar) | 25 | | Material used | HR | HR | C |
| Grain size (mm) | 3 | | Can be used with the following machines Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business | | | |
| SH = shore | 70 | | | | | |
| Stator Ø | 90 | | | | | |
| Length (mm) | 270 | | | | | |





MIXER 6 D6-3



BOOSTER STATOR

STRAIGHT STATOR

ROTOR





| Reference (cat. C4) | 3F00503100 | 3F00503101 | 3F00502800 | 3F00502802 | Ref. (cat. C4) | 7009006000 | 7009307000 | 7009006001 |
|---------------------|------------|-------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------|
| With anti-rotation | - |  | - |  | With anti-rotation | - |  | - |
| Type | D6-3/R6 | | | | Rotor head model |  | | |
| RPM | 400 | | | | | | | |
| Flow-rate (L/min) | 22 | | | | Material used | HR | HR | C |
| Max pressure (bar) | 30 | | | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, I 41, Koine 3 Imer, Koine 4 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business</div> | | | |
| Grain size (mm) | 3 | | | | | | | |
| SH = shore | 70 | | | | | | | |
| Stator Ø | 90 | | | | | | | |
| Length (mm) | 270 | | | | | | | |

MIXER

13

D4-3 D4-1/2



| D4-1/2 | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|-----------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00503000 | 3F00503001 | Ref. (cat. C4) | 7009049700 | 7009108600 | 7009049800 |
| With anti-rotation | - |  | With anti-rotation | - | - | - |
| Type | D4-3 / D4-1/2 | | Rotor head model |  |  |  |
| RPM | 320(*)/400 | | Material used | HR | HR | HR |
| Flow-rate (L/min) | 10(*)/13 | | <div>Can be used with the following machines</div> <div>Mixer Light/Sprinter, Mixpro 28, PFT G4 FU 230V, Ritmo XL FU 230V, M-Tec Mono-Mix, Plus Mono, Compact-Pro 25 (with bayonet rotor), Mai 4Job Business, Mai 4One Sirius Plus</div> | | | |
| Max pressure (bar) | 30 | | | | | |
| Grain size (mm) | 3 | | | | | |
| SH = shore | 70 | | | | | |
| Stator Ø | 90 | | | | | |
| Length (mm) | 270 | | | | | |







(*) speed and flow-rate with single-phased machine

MIXER

26

D4-2









| | STRAIGHT STATOR | | ROTOR | | | | |
|---------------------|-------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00501300 | 3F00501301 | Ref. (cat. C4) | 7009012000 | 7009108300 | 7009011900 | 7009310100 |
| With anti-rotation | - |  | With anti-rotation | - | - | - |  |
| Type | D6-3 Slimline (230 V) /D4-2 (400 V) | | Rotor head model |  |  |  |  |
| RPM | 320(*)/400 | | Material used | HR | HR | HR | HR |
| Flow-rate (L/min) | 16(*)/20 | | | | | | |
| Max pressure (bar) | 25 | | | | | | |
| Grain size (mm) | 3 | | | | | | |
| SH = shore | 70 | | | | | | |
| Stator Ø | 90 | | <div>Can be used with the following machines</div> <div>Mixer Light/Sprinter, Mixpro 28, PFT G4 FU 230V, Ritmo XL FU 230V, M-Tec Mono-Mix, Plus Mono, Compact-Pro 25 (with bayonet rotor), Mai 4Job Business, Mai 4One Sirius Plus</div> | | | | |
| Length (mm) | 270 | | | | | | |

(*) speed and flow-rate with single-phased machine

THE STANDARD MODELS

MIXER 30 D5-2,5 Eco-Star








| | STRAIGHT STATOR | | | ROTOR | | | |
|---------------------|-------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00502900 | 3F00502901 | Ref. (cat. C4) | 7009012500 | 7009108400 | 7009310200 | 7009012600 |
| With anti-rotation | - |  | With anti-rotation | - | - |  | - |
| Type | D5-2,5 / Eco-Star | | Rotor head model |  |  |  |  |
| RPM | 320(*)/400 | | Material used | HR | HR | HR | HR |
| Flow-rate (L/min) | 20(*)/25 | | <div>Can be used with the following machines</div> <div>Mixer Light/Sprinter, Mixpro 28, PFT G4 FU 230V, Ritmo XL FU 230V, M-Tec Mono-Mix, Plus Mono, Compact-Pro 25 (with bayonet rotor), Mai 4Job Business, Mai 4One Sirius Plus</div> | | | | |
| Max pressure (bar) | 20 | | | | | | |
| Grain size (mm) | 3 | | | | | | |
| SH = shore | 70 | | | | | | |
| Stator Ø | 90 | | | | | | |
| Length (mm) | 270 | | | | | | |

(*) speed and flow-rate with single-phased machine

MIXER 32







| | STRAIGHT STATOR | | ROTOR | | | |
|---------------------|-----------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00510500 | 3F00510504 | Ref. (cat. C4) | 7009009000 | 7009310300 | 7009108500 |
| With anti-rotation | - |  | With anti-rotation | - |  | - |
| RPM | 320(*)/400 | | Rotor head model |  |  |  |
| Flow-rate (L/min) | 24(*)/30 | | | | | |
| Max pressure (bar) | 25 | | Material used | HR | HR | HR |
| Grain size (mm) | 3 | | <div>Can be used with the following machines</div> <div>Mixer Light/Sprinter, Mixpro 28, PFT G4 FU 230V, Ritmo XL FU 230V, M-Tec Mono-Mix, Plus Mono, Compact-Pro 25 (with bayonet rotor), Mai 4Job Business, Mai 4One Sirius Plus</div> | | | |
| SH = shore | 60 | | | | | |
| Stator Ø | 90 | | | | | |
| Length (mm) | 270 | | | | | |

(*) speed and flow-rate with single-phased machine

MIXER TAURUS

D5-2,5
D4 MV



| | BOOSTER STATOR | | STRAIGHT STATOR | | | ROTOR | | |
|---------------------|----------------|-----------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00653000 | 3F00653100 | 3F00501200 | 3F00501201 | 3F00501210 | Ref. (cat. C4) | 7009007000 | 7009007200 |
| With anti-rotation | - |  | - |  |  | With anti-rotation | - | |
| Type | D5-2,5 / D4 MV | | | | | Rotor head model |  | |
| RPM | 400 | | | | | Material used | HR | C |
| Flow-rate (L/min) | 24 | | | | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mustang, Mixp 50, PFT G4, Maltec M5, Putzmeister MP 25, Ka 5, VEP VR 6, I 41, Mai 4Job Business, Mai 4C Sirius Plus, Mai 4You Economy Business</div> | | |
| Max pressure (bar) | 25 | | | | | | | |
| Grain size (mm) | 3 | | | | | | | |
| SH = shore | 70 | | | | | | | |
| Stator Ø | 90 | | | | | | | |
| Length (mm) | 270 | | | | | | | |

MIXER MICRO







| | STRAIGHT STATOR | | ROTOR |
|---------------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00500500 | Ref. (cat. C4) | 7009013000 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model | |
| Flow-rate (L/min) | 7 | Material used | HR |
| Max pressure (bar) | 30 | Can be used with the following machines Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business | |
| Grain size (mm) | 2 | | |
| SH = shore | 70 | | |
| Stator Ø | 90 | | |
| Length (mm) | 270 | | |

THE STANDARD MODELS




MIXER PLUS D7-2,5



| | STRAIGHT STATOR | | | | | ROTOR | |
|---------------------|-----------------|-----------------------------------------------------------------------------------|------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00500801 | 3F00500818 | 3F00500813 | 3F00500817 | Ref. (cat. C4) | 7009008000 | 7009304000 |
| With anti-rotation | - |  | - |  | With anti-rotation | - |  |
| Type | D7-2,5 | | Europe | | Rotor head model |  | |
| RPM | | | 400 | | | | |
| Flow-rate (L/min) | | | 26 | | | | |
| Max pressure (bar) | | | 25 | | | | |
| Grain size (mm) | | | 3 | | Material used | HR | |
| SH = shore | 70 | | 60 | | Can be used with the following machines | | |
| Stator Ø | | | 90 | | Plus Top / Standard / Classic, Mixpro 50, PFT G4, Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR 6, Koine 3 Imer, Koine 4 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business | | |
| Length (mm) | | | 270 | | | | |



MIXER POINT D6-3



| | BOOSTER STATOR | | STRAIGHT STATOR | | ROTOR | | |
|---------------------|----------------|-------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00500712 | 3F00500710 | 3F00500700 | 3F00500708 | Ref. (cat. C4) | 7009005000 | 7009005200 |
| With anti-rotation | - |  | - |  | With anti-rotation | - | |
| Type | D6-3 | | | | Rotor head model |  | |
| RPM | 400 | | | | | | |
| Flow-rate (L/min) | 23 | | | | | | |
| Max pressure (bar) | 30 | | | | Material used | HR | C |
| Grain size (mm) | 3 | | | | | | |
| SH = shore | 70 | | | | | | |
| Stator Ø | 90 | | | | | | |
| Length (mm) | 270 | | | | <div>Can be used with the following machines</div> <div>Plus Top / Standard / Classic, Mixpro 50, PFT G Maltec M5, Putzmeister MP 25, Kaleta 5, VEP VR Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business</div> | | |


MIXER POLO D8-1,5



| | STATOR WITH SLITS | STRAIGHT STATOR | ADJUSTABLE STATOR | CLAMPING JACKET | ROTOR | | | |
|---------------------|-------------------|-----------------|-------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|
| Reference (cat. C4) | 3F00503600 | 3F00501000 | 3F00501005 | EUC21311 | Ref. (cat. C4) | 7009011000 | 7009301000 | 7009011200 |
| With anti-rotation | - | - | - | - | With anti-rotation | - |  | - |
| Type | D8-1,5 | | | - | Rotor head model |  | | |
| RPM | 400 | | | - | Material used | HR | HR | C |
| Flow-rate (L/min) | 35 | | | - | Can be used with the following machines CP 30/40, PFT ZP3, M-Tec P 15/20, Swing L, Plus Top - Standard, PFT G4, M5 Maltech, I 41 Fassa, Koine 3 Imer, Koine 4 Imer, Koine 35 Imer, Mai 4Job Business, Mai 4One Sirius Plus, Mai 4You Economy Business | | | |
| Max pressure (bar) | 10 to 20 | 20 | - | - | | | | |
| Grain size (mm) | 3 | | | - | | | | |
| SH = shore | 70 | | | - | | | | |
| Stator Ø | 90 | | | - | | | | |
| Length (mm) | 270 | | | - | | | | |

MAP 5 D8-1,5



| | STRAIGHT STATOR | | ROTOR |
|---------------------|-----------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00529700 | Ref. (cat. C4) | 7009107300 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 35 | Material used | HR |
| Max pressure (bar) | 30 | <div>Can be used with the following machines</div> <div>Europro 24P, MPE 300</div> | |
| Grain size (mm) | 3 | | |
| SH = shore | 70 | | |
| Stator Ø | 90 | | |
| Length (mm) | 270 | | |

THE STANDARD MODELS

MAP 6 D8-1,5




ADJUSTABLE STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00529400 |
| With anti-rotation | D8-1,5 |
| RPM | 400 |
| Flow-rate (L/min) | 35 |
| Max pressure (bar) | 10 to 30 |
| Grain size (mm) | 6 |
| SH = shore | 60 |
| Stator Ø | 90 |
| Length (mm) | 270 |



ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107300 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

Compact-Pro 30, 35, 40

MAP 7 D7-2,5




STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00502313 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 27 |
| Max pressure (bar) | 40 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 90 |
| Length (mm) | 270 |



ROTOR




| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009049406 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

Compact-Pro 30, 35, 40






MIXER 8 SX B4-1,5 L B4-2 L



| | STRAIGHT STATOR | ROTOR | STRAIGHT STATOR | ROTOR | STRAIGHT STATOR | ROTOR |
|-----------------------------------------|-----------------|-----------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------|--------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00600300 | 7009500300 | 3F00528001 | 7009002600 | 3F00528200 | 7009003200 |
| Rotor head model | - |  | - |  | - |  |
| Material used | - | HR | - | HR | - | HR |
| Type | - | - | B4-1,5 L | - | B4-2 L | - |
| RPM | 400 | - | 400 | - | 400 | - |
| Flow-rate (L/min) | 10 | - | 10 | - | 10 | - |
| Max pressure (bar) | 15 | - | 15 | - | 30 | - |
| Grain size (mm) | 2 | - | 2 | - | 2 | - |
| SH = shore | 60 | - | 70 | - | 70 | - |
| Stator Ø | 50 | - | 50 | - | 50 | - |
| Length (mm) | 100 | - | 160 | - | 210 | - |
| Can be used with the following machines | - | | Ritmo M / L | | Putzmeister MP 10, 12, 15, PC 830, Ritmo L | |

MIXER 8 DX N13 S MAP 3 Mini



| | STRAIGHT STATOR | ROTOR | STRAIGHT STATOR | STRAIGHT STATOR | ROTOR | ROTOR | ROTOR | ROTOR |
|---------------------|--------------------------|-------------------------------------------------------------------------------------|-----------------|-----------------|----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00600400 | 7009500400 | 3F00600500 | 3F00528000 | 7009501100 | 7009003500 | 7009500900 | 7009500500 |
| Rotor head model | - |  | - | - |  H 25 |  |  H33,5 |  |
| Material used | - | HR | - | - | HR | HR | HR | INOX |
| Type | N13 S short - MAP 3 Mini | - | N13 S | B4-2 | - | - | - | - |
| RPM | 400 | - | 400 | - | - | - | - | - |
| Flow-rate (L/min) | 10 | - | 10 | - | - | - | - | - |
| Max pressure (bar) | 15 | - | 30 | - | - | - | - | - |
| Grain size (mm) | 2 | - | 2 | - | - | - | - | - |
| SH = shore | 60 | - | 80 | 70 | - | - | - | - |
| Stator Ø | 50 | - | 50 | - | - | - | - | - |
| Length (mm) | 135 | - | 210 | - | - | - | - | - |

THE SPECIAL MODELS

MAP 1




STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00529000 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 5 |
| Max pressure (bar) | 20 |
| Grain size (mm) | 2 |
| SH = shore | 70 |
| Stator Ø | 40 |
| Length (mm) | 170 |



ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines
Polymair

MAP 2 N13 S MK20




STRAIGHT STATOR

| | |
|---------------------|--------------|
| Reference (cat. C4) | 3F00529200 |
| With anti-rotation | - |
| Type | N13 S - MK20 |
| RPM | 400 |
| Flow-rate (L/min) | 10 |
| Max pressure (bar) | 30 |
| Grain size (mm) | 2 |
| SH = shore | 70 |
| Stator Ø | 50 |
| Length (mm) | 210 |




ROTOR

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107100 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines
Europro 8P, PC8, Kosner MK20


MAP 3 N13 S MK20



| | STRAIGHT STATOR | | STATOR WITH SLITS | CLAMPING JACKET | ROTOR | |
|---------------------|-----------------|------------|-------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00529201 | 3F00528800 | 3F00528900 | EUC21265 | Ref. (cat. C4) | 7009107800 |
| With anti-rotation | - | | | - | With anti-rotation | - |
| Type | N13 S - MK20 | | | - | Rotor head model |  |
| RPM | 400 | | | - | Material used | HR |
| Flow-rate (L/min) | 10 | | | - | Can be used with the following machines Europro 4P, Mixpro 14, CP 10 & 15, Optimix 30, PC 830, Putzmeister MP 10, 12, 15, Compact-Pro Joint 10, Kosner MK20 | |
| Max pressure (bar) | 20 | | 10 to 30 | - | | |
| Grain size (mm) | 2 | | | - | | |
| SH = shore | 60 | 70 | 60 | - | | |
| Stator Ø | 50 | | | - | | |
| Length (mm) | 210 | | | - | | |

MAP 4



| | STRAIGHT STATOR | | ROTOR |
|---------------------|-----------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00529300 | Ref. (cat. C4) | 7009107200 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 9 | Material used | HR |
| Max pressure (bar) | 40 | Can be used with the following machines Europro 14P | |
| Grain size (mm) | 2 | | |
| SH = shore | 70 | | |
| Stator Ø | 60 | | |
| Length (mm) | 265 | | |

THE SPECIAL MODELS

MAP 12




STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00509900 |
| With anti-rotation | - |
| RPM | 30(*)/400 |
| Flow-rate (L/min) | 0.1(*)/1.4 |
| Max pressure (bar) | 10 |
| Grain size (mm) | 1 |
| SH = shore | 70 |
| Stator Ø | 27 |
| Length (mm) | 120 |

(*) speed and flow rate with RPM indicated




ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009265200 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | INOX |

Can be used
with the following machines

TwinMix

Don't forget



Essential:


Reference (cat. C5)
3M07701000

ANTIGRIP

To facilitate the assembly
of every models of rotors


KOSNER MK140



| | STRAIGHT STATOR | | ROTOR |
|---------------------|-----------------|-------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00660300 | Ref. (cat. C4) | 7009501500 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 21 | Material used | HR |
| Max pressure (bar) | 30 | <div>Can be used with the following machines</div> <div>Kosner MK30, Kosner MK40, Kosner MK140, Kosner MK50</div> | |
| Grain size (mm) | 3 | | |
| SH = shore | 80 | | |
| Stator Ø | 59 | | |
| Length (mm) | 260 | | |

KOSNER MK80



| | STRAIGHT STATOR | | ROTOR |
|---------------------|-----------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00660200 | Ref. (cat. C4) | 7009501400 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 35 | Material used | HR |
| Max pressure (bar) | 30 | <div>Can be used with the following machines</div> <div>Kosner MK80, Kosner MK60</div> | |
| Grain size (mm) | 3 | | |
| SH = shore | 80 | | |
| Stator Ø | 82,5 | | |
| Length (mm) | 285 | | |


MIXER CAOUT 19



STRAIGHT STATOR

ROTOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00651100 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 19 |
| Max pressure (bar) | - |
| Grain size (mm) | 2 |
| SH = shore | 70 |
| Stator Ø | 80 |
| Length (mm) | 259 |

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009251100 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | C |

Can be used
with the following machines

Hemo


PC 830



STRAIGHT STATOR

ROTOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00591000 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 12 |
| Max pressure (bar) | 40 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 50 |
| Length (mm) | 135 |

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009401000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

PlastCoat PC 830, PlastCoat PC 430


W 10/2,5



STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00592000 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 20 |
| Max pressure (bar) | 25 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 90 |
| Length (mm) | 270 |

ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009402000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

PlastCoat PC 25E, PlastCoat PC 35E


W 10/3



STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00590000 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 22 |
| Max pressure (bar) | 30 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 90 |
| Length (mm) | 270 |

ROTOR

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009400000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

PlastCoat PC 25E, PlastCoat PC 35E

THE SPECIAL MODELS

W 20/1,5




ADJUSTABLE STATOR



ROTOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00593000 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 35 |
| Max pressure (bar) | 20 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 90 |
| Length (mm) | 270 |

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009403000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines
PlastCoat PC 25E, PlastCoat PC 35E

MIXER D5




STATOR WITH SLITS



ROTOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00500300 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 33 |
| Max pressure (bar) | 10 to 20 |
| Grain size (mm) | 4 |
| SH = shore | 70 |
| Stator Ø | 90 |
| Length (mm) | 350 |

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009003600 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines
SPG Baumaschinen - Putzmeister S5



MIXER MP3L



STRAIGHT STATOR



ROTOR

| | | | |
|---------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00508100 | Ref. (cat. C7) | 7009024001 |
| With anti-rotation |  | With anti-rotation | - |
| RPM | 400 | Rotor head model |  25 x 25 x h 38 |
| Flow-rate (L/min) | 22 | Material used | HR |
| Max pressure (bar) | 30 | <div>Can be used with the following machines</div> <div>Mai 440 HD</div> | |
| Grain size (mm) | 4 | | |
| SH = shore | 70 | | |
| Stator Ø | 101 | | |
| Length (mm) | 374 | | |



MIXER MP8L



STRAIGHT STATOR



ROTOR

| | | | |
|---------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00508001 | Ref. (cat. C7) | 7009020000 |
| With anti-rotation |  | With anti-rotation | - |
| RPM | 400 | Rotor head model |  25 x 25 x h 40 |
| Flow-rate (L/min) | 40 | Material used | HR |
| Max pressure (bar) | 30 | <div>Can be used with the following machines</div> <div>Mai 440 GE, Mai 440 NT, Mai 440 HD</div> | |
| Grain size (mm) | 7 | | |
| SH = shore | 70 | | |
| Stator Ø | 101 | | |
| Length (mm) | 374 | | |

THE SPECIAL MODELS

MIXER MP12L



STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C7) | 3F00507001 |
| With anti-rotation | |
| RPM | 400 |
| Flow-rate (L/min) | 60 |
| Max pressure (bar) | 30 |
| Grain size (mm) | 7 |
| SH = shore | 70 |
| Stator Ø | 101 |
| Length (mm) | 535 |



ROTOR

| | |
|--------------------|--------------------|
| Ref. (cat. C7) | 7009021001 |
| With anti-rotation | - |
| Rotor head model | 25 x 25 x h 40 |
| Material used | HR |

Can be used
with the following machines
Mai 440 GE, Mai 440 NT, Mai 440 HD

MIXER MP40 49/15



STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C7) | 3F00600000 |
| With anti-rotation | |
| Type | 49/15 |
| RPM | 400 |
| Flow-rate (L/min) | 250 |
| Max pressure (bar) | 30 |
| Grain size (mm) | 8 |
| SH = shore | 60 |
| Stator Ø | 166 |
| Length (mm) | 455 |



ROTOR

| | |
|--------------------|--------------------|
| Ref. (cat. C7) | 7009500000 |
| With anti-rotation | - |
| Rotor head model | 38 x 38 x h 40 |
| Material used | HR |


JET 1



STRAIGHT STATOR

| | | |
|---------------------|------------|------------|
| Reference (cat. C4) | 3F00529800 | 3F00529801 |
| With anti-rotation | - | - |
| RPM | 400 | |
| Flow-rate (L/min) | 10 | |
| Max pressure (bar) | 100 | 80 |
| Grain size (mm) | 2 | |
| SH = shore | 70 | 60 |
| Stator Ø | 50 | |
| Length (mm) | 310 | |

ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107500 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

Jetpro 80, Flatspray 10


JET 2



STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00529100 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 10 |
| Max pressure (bar) | 140 |
| Grain size (mm) | 2 |
| SH = shore | 80 |
| Stator Ø | 50 |
| Length (mm) | 310 |

CHROMED ROTOR

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107700 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

Can be used
with the following machines

Jetpro 100, Jetmix 100, Flatmix 100, Flatspray 20

THE HIGH PRESSURE MODELS

JET 3





STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00503011 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 13 |
| Max pressure (bar) | 160 |
| Grain size (mm) | 3 |
| SH = shore | 80 |
| Stator Ø | 70 |
| Length (mm) | 408 |



CHROMED ROTOR

| | | |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009050200 | 7009108800 |
| With anti-rotation | - | - |
| Rotor head model |  |  |
| Material used | C | |

hexagon 24 mm

Can be used
with the following machines
Jetpro 120, Jetbag 130, Flatspray 30

JET 4



BOOSTER STATOR




STRAIGHT STATOR

| | | |
|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00529500 | 3F00529900 |
| With anti-rotation |  |  |
| RPM | 400 | |
| Flow-rate (L/min) | 21 | |
| Max pressure (bar) | 160 | 140 |
| Grain size (mm) | 3 | |
| SH = shore | 80 | |
| Stator Ø | 90 | |
| Length (mm) | 450 | |



CHROMED ROTOR

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009107600 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | C |

Can be used
with the following machines
Jetpro 160, Jetbag 160


JET 5



BOOSTER STATOR

STRAIGHT STATOR

CHROMED ROTOR

| | | | | |
|----------------------------|------------|------------|---------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00560600 | 3F00560300 | Ref. (cat. C4) | 7009106900 |
| With anti-rotation | - | - | With anti-rotation | - |
| RPM | 400 | | Rotor head model |  |
| Flow-rate (L/min) | 13 | | Material used | C |
| Max pressure (bar) | 140 | | | |
| Grain size (mm) | 3 | | | |
| SH = shore | 80 | | | |
| Stator Ø | 70 | | | |
| Length (mm) | 408 | | | |

JET 6

4N13S

Köbra 690



STRAIGHT STATOR

CHROMED ROTOR

| | | | |
|----------------------------|-------------------|---------------------------|------------|
| Reference (cat. C4) | 3F00528100 | Ref. (cat. C4) | 7009002800 |
| With anti-rotation | - | With anti-rotation | - |
| Type | 4N13S - Köbra 690 | | |
| RPM | 400 | | |
| Flow-rate (L/min) | 10 | | |
| Max pressure (bar) | 150 | | |
| Grain size (mm) | 2 | | |
| SH = shore | 70 | | |
| Stator Ø | 50 | | |
| Length (mm) | 408 | | |

**Can be used
with the following machines**

Köbra 690, HP 30

THE HIGH PRESSURE MODELS

24-4 HP




STRAIGHT STATOR

| | |
|---------------------|------------|
| Reference (cat. C4) | 3F00560700 |
| With anti-rotation | - |
| RPM | 400 |
| Flow-rate (L/min) | 10 |
| Max pressure (bar) | 150 |
| Grain size (mm) | 2 |
| SH = shore | 70 |
| Stator Ø | 60 |
| Length (mm) | 411 |




ROTOR

| | |
|--------------------|-------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009109100 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |

MIXER VG 55-11




STRAIGHT STATOR

| | |
|---------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C4) | 3F00520000 |
| With anti-rotation |  |
| RPM | 400 |
| Flow-rate (L/min) | 24 |
| Max pressure (bar) | 150 |
| Grain size (mm) | 3 |
| SH = shore | 70 |
| Stator Ø | 101 |
| Length (mm) | 535 |



ROTOR

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Ref. (cat. C4) | 7009023000 |
| With anti-rotation | - |
| Rotor head model |  |
| Material used | HR |


Can be used
with the following machines

Mai 4Spark



MIXER 1L6





| | STATOR WITH SLITS | | ROTOR |
|---------------------|-------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00506300 | Ref. (cat. C7) | 7009009200 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 320(*)/400 | Rotor head model |  Ø 59 |
| Flow-rate (L/min) | 48(*)/60 | Material used | - |
| Max pressure (bar) | 10 to 30 | <div>Can be used with the following machines</div> <div>SP 5 Putzmeister</div> | |
| Grain size (mm) | 7 | | |
| SH = shore | 60 | | |
| Stator Ø | 101 | | |
| Length (mm) | 265 | | |

(*) speed and flow-rate with single-phased machine



MIXER 2L6 MAP10



| | STATOR WITH SLITS | ADJUSTABLE STATOR | STRAIGHT STATOR | CLAMPING JACKET | | ROTOR |
|---------------------|-------------------|-------------------|-------------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00501400 | 3F00501403 | 3F00501402 | EUC20766 | Ref. (cat. C7) | 7009108000 |
| With anti-rotation | - | - |  | - | With anti-rotation | - |
| Type | | 2L6 - MAP 10 | | - | Rotor head model |  Ø 54 |
| RPM | | 400 | | - | Material used | HR |
| Flow-rate (L/min) | | 60 | | - | <div>Can be used with the following machines</div> <div>Compact-Pro 60, Putzmeister SP 5 & SP 11, Lancy PH 9, Bunker S28R, Cura 3900</div> | |
| Max pressure (bar) | 0 to 20 | | 20 | - | | |
| Grain size (mm) | | 7 | | - | | |
| SH = shore | | 60 | | - | | |
| Stator Ø | | 101 | | - | | |
| Length (mm) | | 535 | | - | | |

THE HIGH OUTPUT MODELS

MAP 11 JUMBO



| | ADJUSTABLE STATOR | STATOR WITH SLITS | STRAIGHT STATOR | | ROTOR |
|---------------------|-------------------|-------------------|-----------------|--------------------|------------|
| Reference (cat. C7) | 3F00503900 | 3F00503800 | 3F00505100 | Ref. (cat. C7) | 7009008800 |
| With anti-rotation | - | - | | With anti-rotation | - |
| RPM | | 400 | | | |
| Flow-rate (L/min) | | 90 | | Rotor head model | Ø 54 |
| Max pressure (bar) | | 10 to 30 | 20 | Material used | HR |
| Grain size (mm) | | 6 | | | |
| SH = shore | | 60 | | | |
| Stator Ø | | 101 | | | |
| Length (mm) | | 535 | | | |

Can be used with the following machines

Compact-Pro 60, Putzmeister SP 5 & SP 11, Lancy PH 9, Bunker S28R, Cura 3900, Optimix 20 (5,5)

MIXER 2L6 +++





| | STATOR WITH SLITS | ADJUSTABLE STATOR | STRAIGHT STATOR | CLAMPING JACKET | | ROTOR |
|---------------------|-------------------|-------------------|-----------------|-----------------|----------|---------------------------|
| Reference (cat. C7) | 3F00506400 | 3F00506200 | 3F00506500 | 3F00506600 | EUC20766 | Ref. (cat. C7) 7009009300 |
| With anti-rotation | - | - | | - | - | With anti-rotation - |
| Type | | 2L6+++ | | - | | |
| RPM | | 400 | | - | | Rotor head model Ø 54 |
| Flow-rate (L/min) | | 110 | | - | | |
| Max pressure (bar) | | 10 to 30 | 20 | - | | Material used HR |
| Grain size (mm) | | 7 | | - | | |
| SH = shore | | 60 | | - | | |
| Stator Ø | | 101 | | - | | |
| Length (mm) | | 535 | | - | | |

Can be used with the following machines

Compact-Pro 60, Putzmeister SP 5 & SP 11, Lancy PH 9, Bunker S28R, Cura 3900, Optimix 20 (5,5), Ster 120 Imer, Prestige Imer, S5 EVTM Putzmeister, SP11 LMR Putzmeister


MIXER BORA 50/7/R



| | ADJUSTABLE STATOR | STRAIGHT STATOR | ROTOR | |
|---------------------|-------------------|-----------------------------------------------------------------------------------|--------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520210 | 3F00520205 | Ref. (cat. C7) | 7009017000 |
| With anti-rotation | - |  | With anti-rotation | - |
| Type | - | 50/7/R | Rotor head model |  |
| RPM | | 400 | | |
| Flow-rate (L/min) | | 60 | | |
| Max pressure (bar) | 10 to 30 | 30 | | |
| Grain size (mm) | | 8 | Material used | HR |
| SH = shore | | 70 | | |
| Stator Ø | | 101 | | |
| Length (mm) | | 535 | | |

MIXER JUMBO



| | ADJUSTABLE STATOR | ROTOR | |
|---------------------|-------------------|--------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00505800 | Ref. (cat. C7) | 7009009400 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 90 | Material used | HR |
| Max pressure (bar) | 10 to 30 | | |
| Grain size (mm) | 7 | | |
| SH = shore | 60 | | |
| Stator Ø | 101 | | |
| Length (mm) | 535 | | |

Can be used
with the following machines

Jetpro 100, Jetmix 100, Flatmix 100, Flatspray 20

THE HIGH OUTPUT MODELS

MIXER VIPER DX SHORT



| | STRAIGHT STATOR | | | | ROTOR | | |
|---------------------|-----------------|------------|------------|-----------------------------------------|------------|------------|------------|
| Reference (cat. C7) | 3F00522100 | 3F00522500 | 3F00522600 | Ref. (cat. C7) | 7009043000 | 7009043900 | 7009044300 |
| With anti-rotation | | | | With anti-rotation | - | | |
| RPM | | 400 | | Rotor head model | | | |
| Flow-rate (L/min) | | 55 | | Material used | HR | HR | HR |
| Max pressure (bar) | | 20 | 15 | Can be used with the following machines | | | |
| Grain size (mm) | | 7 | | | | | |
| SH = shore | | 70 | 60 | | | | |
| Stator Ø | 101 | | 114 | | | | |
| Length (mm) | | 265 | | | | | |

| Can be used with the following machines | |
|-----------------------------------------|-------|
| M-Tec M300 | Remix |

MIXER VIPER SX SHORT



MAP 8



MAP 8

| | STRAIGHT STATOR | | | ROTOR | | |
|---------------------|-----------------|------------|-----------------------------------------|------------|------------|------------|
| Reference (cat. C7) | 3F00522200 | 3F00522201 | Ref. (cat. C7) | 7009043700 | 7009044200 | 7009043500 |
| With anti-rotation | | - | With anti-rotation | - | - | - |
| RPM | | 400 | Rotor head model | | | |
| Flow-rate (L/min) | | 55 | Material used | HR | HR | HR |
| Max pressure (bar) | | 20 | Can be used with the following machines | | | |
| Grain size (mm) | | 7 | | | | |
| SH = shore | | 70 | | | | |
| Stator Ø | | 101 | | | | |
| Length (mm) | | 265 | | | | |

| Can be used with the following machines | | |
|-----------------------------------------|------------------|---|
| Compact-Pro 60 | Mixer Optimix 20 | - |

MIXER VIPER DX LONG

2L88 / Megastar



STRAIGHT STATOR

ROTOR

| | | |
|---------------------|-----------------|------------|
| Reference (cat. C7) | 3F00520806 | 3F00520804 |
| With anti-rotation | | |
| Type | 2L88 / Megastar | |
| RPM | 400 | |
| Flow-rate (L/min) | 55 | |
| Max pressure (bar) | 30 | |
| Grain size (mm) | 7 | |
| SH = shore | 70 | |
| Stator Ø | 101 | 114 |
| Length (mm) | 535 | |

| | |
|--------------------|------------|
| Ref. (cat. C7) | 7009015000 |
| With anti-rotation | - |
| Rotor head model | |
| Material used | HR |

Can be used
with the following machines

Compact-Pro 60, Putzmeister SP 5 & SP 11, Lancy PH 9,
Bunker S28R, Cura 3900

MIXER VIPER SX LONG



STRAIGHT STATOR

ROTOR

| | | |
|---------------------|------------|------------|
| Reference (cat. C7) | 3F00520808 | 3F00520807 |
| With anti-rotation | | |
| RPM | 400 | |
| Flow-rate (L/min) | 55 | |
| Max pressure (bar) | 30 | |
| Grain size (mm) | 7 | |
| SH = shore | 70 | |
| Stator Ø | 101 | 114 |
| Length (mm) | 535 | |

| | | | |
|--------------------|------------|------------|------------|
| Ref. (cat. C7) | 7009015903 | 7009015905 | 7009015904 |
| With anti-rotation | - | - | - |
| Rotor head model | | | |
| Material used | HR | HR | HR |

Can be used
with the following machines

- Mixer Optimix
20 -

THE HIGH OUTPUT MODELS



MIXER BORA SHORT R7 – 1,5



ADJUSTABLE STATOR



ROTOR

| | | | | |
|---------------------|------------|---------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00600900 | Ref. (cat. C7) | 7009500200 | 7009310500 |
| With anti-rotation | - | With anti-rotation | - |  |
| Type | R 7 - 1,5 | Rotor head model |  | |
| RPM | 400 | Material used | HR | HR |
| Flow-rate (L/min) | 60 | Can be used with the following machines PFT G4, PFT Ritmo, PTF Swing L, PFT ZP3, Duomix | | |
| Max pressure (bar) | 10 to 20 | | | |
| Grain size (mm) | 8 | | | |
| SH = shore | 70 | | | |
| Stator Ø | 114 | | | |
| Length (mm) | 270 | | | |


MAP 9



ADJUSTABLE STATOR







ROTOR

| | | | |
|---------------------|------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00529600 | Ref. (cat. C7) | 7009107400 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 200 | Material used | HR |
| Max pressure (bar) | 10 to 30 | Can be used with the following machines Compact-Pro 60 | |
| Grain size (mm) | 8 | | |
| SH = shore | 60 | | |
| Stator Ø | 125 | | |
| Length (mm) | 500 | | |


MIXER BORA 50 – 7R SHORT 15/14UU



| ADJUSTABLE STATOR | | ROTOR | | | |
|---------------------|------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00600200 | Ref. (cat. C7) | 7009500200 | 7009310500 | 7009017200 |
| With anti-rotation | - | With anti-rotation | - |  | - |
| Type | 15/14UU | Rotor head model |  |  |  |
| RPM | 400 | Material used | HR | HR | C |
| Flow-rate (L/min) | 60 | <div>Can be used with the following machines</div> <div>M-Tec M300 - Duomix</div> | | | |
| Max pressure (bar) | 10 to 20 | | | | |
| Grain size (mm) | 8 | | | | |
| SH = shore | 70 | | | | |
| Stator Ø | 125 | | | | |
| Length (mm) | 270 | | | | |


MIXER BORA 50 – 7R LONG



| ADJUSTABLE STATOR | | ROTOR | |
|---------------------|------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520202 | Ref. (cat. C7) | 7009017000 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 60 | Material used | HR |
| Max pressure (bar) | 10 to 30 | <div>Can be used with the following machines</div> <div>M-Tec P50, M-Tec Silomischpumpe (SMP)</div> | |
| Grain size (mm) | 8 | | |
| SH = shore | 70 | | |
| Stator Ø | 125 | | |
| Length (mm) | 535 | | |


MIXER MIRAGE /75 SHORT



| | ADJUSTABLE STATOR | | ROTOR |
|---------------------|-------------------|--------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520500 | Ref. (cat. C7) | 7009105700 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 80 | Material used | HR |
| Max pressure (bar) | 10 to 30 | | |
| Grain size (mm) | 8 | | |
| SH = shore | 70 | | |
| Stator Ø | 125 | | |
| Length (mm) | 270 | | |



MIXER MIRAGE /75 LONG



| | ADJUSTABLE STATOR | | ROTOR |
|---------------------|-------------------|--------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520505 | Ref. (cat. C7) | 7009105800 |
| With anti-rotation | - | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 80 | Material used | HR |
| Max pressure (bar) | 10 to 30 | | |
| Grain size (mm) | 8 | | |
| SH = shore | 70 | | |
| Stator Ø | 125 | | |
| Length (mm) | 535 | | |




MIXER MIRAGE SHORT Ü356 short



| | STRAIGHT STATOR | ADJUSTABLE STATOR | | ROTOR | |
|---------------------|-----------------|-------------------|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520408 | 3F00520418 | Ref. (cat. C7) | 7009105301 | 7009105400 |
| With anti-rotation | - | - | With anti-rotation | - | - |
| Type | Ü356 short | | Rotor head model |  |  |
| RPM | 400 | | Material used | HR | HR |
| Flow-rate (L/min) | 140 | | | | |
| Max pressure (bar) | 30 | 10 to 30 | | | |
| Grain size (mm) | 8 | | | | |
| SH = shore | 70 | | | | |
| Stator Ø | 125 | | | | |
| Length (mm) | 270 | | | | |

MIXER MIRAGE LONG Ü356/Uni-star 3



| | STRAIGHT STATOR | ADJUSTABLE STATOR | | ROTOR | | |
|---------------------|-------------------|-------------------|--------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520405 | 3F00520415 | Ref. (cat. C7) | 7009105201 | 7009105500 | 7009105205 |
| With anti-rotation | - | - | With anti-rotation | - | - | - |
| Type | Ü356 / Uni-star 3 | | Rotor head model |  |  |  |
| RPM | 400 | | Material used | HR | HR | HR |
| Flow-rate (L/min) | 140 | | | | | |
| Max pressure (bar) | 30 | 10 to 30 | | | | |
| Grain size (mm) | 8 | | | | | |
| SH = shore | 70 | | | | | |
| Stator Ø | 125 | | | | | |
| Length (mm) | 535 | | | | | |

Can be used
with the following machines
M-Tec Silomischpumpe (SMP)

THE HIGH OUTPUT MODELS

MIXER 2L74



STRAIGHT STATOR

ADJUSTABLE STATOR

ROTOR

Reference (cat. C7)

3F00501902

3F00501903

Ref. (cat. C7)

7009106000

7009106600

With anti-rotation



-

With anti-rotation

-

RPM

400

Flow-rate (L/min)

200

Rotor head model



Max pressure (bar)

25

Material used

HR

Grain size (mm)

8

SH = shore

60

Stator Ø

125

Length (mm)

666

Can be used with the following machines

SP 11 BHF

MIXER 2L75



ADJUSTABLE STATOR

ROTOR

Reference (cat. C7)

3F00551000

Ref. (cat. C7)

7009501300

With anti-rotation

-

With anti-rotation

-

RPM

400

Flow-rate (L/min)

250

Rotor head model



Max pressure (bar)

20

Material used

HR

Grain size (mm)

8

SH = shore

60

Stator Ø

125

Length (mm)

666

Can be used with the following machines

Putzmeister SP25 DQR



MIXER OSCAR



ADJUSTABLE STATOR



ROTOR

| | | | |
|---------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00504000 | Ref. (cat. C7) | 7009028000 |
| With anti-rotation |  | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 240 | Material used | HR |
| Max pressure (bar) | 10 to 30 | <div>Can be used with the following machines</div> <div>M-Tec Silomischpumpe (SMP)</div> | |
| Grain size (mm) | 8 | | |
| SH = shore | 70 | | |
| Stator Ø | 145 | | |
| Length (mm) | 497 | | |



MIXER BIG FOOT



ADJUSTABLE STATOR



ROTOR

| | | | |
|---------------------|-------------------------------------------------------------------------------------|--------------------|---------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00509400 | Ref. (cat. C7) | 7009031000 |
| With anti-rotation |  | With anti-rotation | - |
| RPM | 400 | Rotor head model |  |
| Flow-rate (L/min) | 300 | Material used | HR |
| Max pressure (bar) | 10 to 30 | | |
| Grain size (mm) | 9 | | |
| SH = shore | 70 | | |
| Stator Ø | 145 | | |
| Length (mm) | 497 | | |

THE HIGH OUTPUT MODELS

MIXER ESTRICH STAR



ADJUSTABLE STATOR

Reference (cat. C7)

3F00520600

With anti-rotation



Type

Estrich star

RPM

400

Flow-rate (L/min)

220

Max pressure (bar)

10 to 25

Grain size (mm)

9

SH = shore

70

Stator Ø

145

Length (mm)

497



ROTOR

Ref. (cat. C7)

7009016000

With anti-rotation

-

Rotor head model



Material used

HR

Can be used
with the following machines

M-Tec Silomischpumpe (SMP)

MIXER MAGNUM Betonstar 2



ADJUSTABLE STATOR

Reference (cat. C7)

3F00509300

With anti-rotation



Type

Betonstar 2

RPM

400

Flow-rate (L/min)

200

Max pressure (bar)

10 to 30

Grain size (mm)

8

SH = shore

60

Stator Ø

145

Length (mm)

497



ROTOR

Ref. (cat. C7)

7009027000

With anti-rotation

-

Rotor head model






Material used

HR



60-12 PLUS







| | STRAIGHT STATOR | | ADJUSTABLE STATOR | | ROTOR | | |
|---------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------|------------|--------------------|-------------------------------------------------------------------------------------|------------|
| Reference (cat. C7) | 3F00508400 | 3F00563500 | 3F00508300 | 3F00563000 | Ref. (cat. C7) | 7009200000 | 7009200100 |
| With anti-rotation |  |  | - | - | With anti-rotation | - | - |
| RPM | 400 | | | | Rotor head model |  | |
| Flow-rate (L/min) | 326 | | | | | | |
| Max pressure (bar) | 30 | | 10 to 30 | | | | |
| Grain size (mm) | 10 | | | | | | |
| SH = shore | 60 | | | | Length (mm) | 620 | 750 |
| Stator Ø | 145 | | | | | | |
| Length (mm) | 535 | 666 | 535 | 666 | | | |



MIXER 75-15 1,5L7



| | STRAIGHT STATOR | | ADJUSTABLE STATOR | STRAIGHT STATOR | ADJUSTABLE STATOR | ROTOR | |
|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------------------------------|-------------------|--------------------|------------------------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00520910 | 3F00520900 | 3F00520901 | 3F00520904 | 3F00520902 | Ref. (cat. C7) | 7009054000 |
| With anti-rotation |  |  | - |  | - | With anti-rotation | - |
| Type | 1,5 L7 | | | | | Rotor head model |  52,5 x h 59 |
| RPM | 400 | | | | | | |
| Flow-rate (L/min) | 300 | | | | | | |
| Max pressure (bar) | 30 | 35 | 10 to 35 | 35 | 10 to 35 | Material used | HR |
| Grain size (mm) | 8 | | | | | | |
| SH = shore | 50 | 60 | | 70 | | | |
| Stator Ø | 159 | | | | | | |
| Length (mm) | 550 | | | | | | |

THE HIGH OUTPUT MODELS


MIXER 1,5 L8



ADJUSTABLE STATOR

ROTOR

| | |
|---------------------|------------|
| Reference (cat. C7) | 3F00601100 |
| With anti-rotation | - |
| Type | 1,5 L8 |
| RPM | 400 |
| Flow-rate (L/min) | 580 |
| Max pressure (bar) | 10 to 30 |
| Grain size (mm) | 14 |
| SH = shore | 60 |
| Stator Ø | 190 |
| Length (mm) | 650 |

| | |
|--------------------|-------------------------------------------------------------------------------------------------------|
| Ref. (cat. C7) | 7009210000 |
| With anti-rotation | - |
| Rotor head model |  59 x 59 x h 50 |
| Material used | HR |

Can be used
with the following machines
Putzmeister S8


MIXER 2L8





ADJUSTABLE STATOR

STRAIGHT STATOR

ROTORE

| | | | |
|---------------------|------------|------------|-------------------------------------------------------------------------------------|
| Reference (cat. C7) | 3F00600100 | 3F00601500 | 3F00601300 |
| With anti-rotation | - | - |  |
| Type | 2L8 | | |
| RPM | 400 | | |
| Flow-rate (L/min) | 450 | | |
| Max pressure (bar) | 10 to 30 | | 30 |
| Grain size (mm) | 14 | | |
| SH = shore | 60 | 70 | 60 |
| Stator Ø | 190 | | |
| Length (mm) | 650 | | |

| | | |
|--------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Ref. (cat. C7) | 7009500100 | 7009500700 |
| With anti-rotation | - | - |
| Type | - | 2L8 |
| Rotor head model |  51,5 x h 52 |  59 x 59 x h 50 |
| Material used | HR | HR |

Can be used
with the following machines
X-Pro D200, Putzmeister SP 20 DHF

Stay updated on our website



Summary staters table



Advertising materials

General Terms and Conditions of Sale

These general terms and conditions apply to every sale and supply of goods between:

Mixer Technology S.r.l., with registered office in Torri di Quartesolo (province of Vicenza, Italy) Via Dei Carabinieri no. 44/45, tax code and VAT no. 03725830248, in person of its legal representative Mr. Patrick Borel, building machinery company and exclusive distributor of the EUROMAIR brand for Italy, hereinafter called the Supplier and the company called the "Purchaser". The Supplier and the Purchaser are collectively referred to as the "Parties"

Whereas

a. The Purchaser is an Italian-law company dealing with the wholesale of machinery, equipment, technical appliances, construction materials and goods sold in Italy and abroad (the "Products" or "Materials"), as per catalog and / or products that can be viewed on our website www.mixersrl.com, and which forms an integral part of the same (Appendix A);

b. The Purchaser is interested in buying the Products from the Supplier;

c. the Supplier shall supply the Products using its own efficient organisation, resources and personnel and confirms that it has adequate planning, production - related and organisational capabilities.

d. The relationship between the Parties shall be fully independent, both in economic and financial terms, and with this Agreement they intend to stipulate the conditions for the supply of the Materials only.

Therefore the Parties agree as follows.

1) Premises

The premises and the annexes are integral and essential parts of this agreement.

2) Conditions agreed between the Parties

2.1 These Terms and Conditions shall apply to and are integral parts of every order commissioned by the Purchaser and they will regulate the relationship between the Parties. The application of other agreements is expressly forbidden and any amendments to this Agreement must be settled in writing. 2.2 The Supplier's offers and/or quotations aren't binding. The information supplied in the catalogues, brochures and pricelists are non-binding and may be modified by

the Supplier; for each purchase, reference should be made to the specific context of the purchase order and corresponding confirmation.

3) Object

The Supplier shall supply its products to the Purchaser who hereby agrees to buy them, under the terms and conditions of this Agreement, with the purpose of marketing them. Anyway, the Supplier will not be held liable or in default for late or non-delivery, except in cases of fraud or gross negligence.

4) Orders and order confirmations

4.1 The orders of the Purchaser shall indicate the number of the order, the exact description of the ordered goods and the product code, quantity, unit and total price, terms of payment, destination and any other instructions for the delivery. The Supplier shall not be held liable for non-delivery due to the incomplete or inaccurate compilation of the purchase order by the Purchaser. The Purchaser which is established in Italy shall indicate exactly its personal data as well as the "recipient code" for the purposes of subsequent electronic invoicing. 4.2 The order is deemed accepted from the Supplier when the Purchaser receives the Order Confirmation. The sale contract will be concluded when the Purchaser accepts the Order Confirmation or, in any case, after three days from the Order Confirmation sending, without any Purchaser's communication of revocation, cancellation or termination.

5) Characteristics of products

5.1 In issuing the purchase order, the Purchaser acknowledges to have carefully analysed the technical, functional and aesthetic characteristics of the Products and to deem them suitable for the purpose they will be directly or indirectly used for.

5.2 With specific written approval from the Supplier, which shall be considered an essential condition, the sale of a Product may be preceded by a demonstration; in that case, only the Supplier operators shall be authorised to handle the equipment during the demonstration. The Purchaser will provide, at its own expenses, the resources and products useful for the demonstration (e.g. power, water, air, paints, coatings etc.). The Purchaser will take all the necessary precautions in order to guarantee the safety of personnel during the demonstration, and the Supplier may not be held liable for any injury to people and/or damage to property.

6) Delivery

6.1 Unless otherwise indicated, the delivery shall be Ex Works from the site in Torri di Quartesolo (province of Vicenza, Italy), Via dei Carabinieri n. 44/45. From the delivery to the Purchaser, to the courier or to the carrier and, in any case, from the moment the products are made available to the Purchaser, the risk of their loss shall be passed to the Purchaser.

6.2 Unless expressly agreed otherwise, the terms of delivery are provisional and non-binding.

6.3 Delays in delivery may not entitle the Purchaser to terminate the sale, or ask for compensation for damage and/or interest.

6.4 In case of missed withdrawal or in case of impossibility to deliver the Products not attributable to the Supplier, if the materials are stored in the Supplier's premises, the Purchaser shall pay a penalty for delay, in addition to the value of the supplies, in an amount equal to 0.5% of the not delivered goods total value for each week of storage after the first 10 days; the Supplier will be entitled to keep the materials until the receipt of the payment of the penalty for delay; furthermore the order may be terminated due to fault of the Purchaser, pursuant to article 1456 civil code.

7) Communications

Orders, order confirmations, waybills and invoices will be exchanged as hardcopies (by fax) or by email. To the Purchaser which is established in the Italian territory, the invoices will be sent through the SDI system managed by the Inland Revenue.

8) Prices and terms of payment

Prices and terms of payments are indicated in the order confirmation and stated on each invoice. If the order confirmation provides for one or more payments prior to the delivery of products, non-payment of such advances on the agreed dates shall entitle the Supplier to suspend the delivery and/or any other activity, without prejudice to the Supplier's right to compensation for damages.

9) Delayed payment or non-payment

9.1 The payment will be due entirely within the agreed terms even in case of delayed delivery or in case of damage or loss during transportation, not attributable to the Supplier.

9.2 In case of delayed payment, the Supplier may suspend every further delivery.

9.3 The non-payment of even a single invoice on its due date shall result that all the other outstanding invoices become immediately due and payable, pursuant to art. 1186 civil code, even if the invoices are related to different orders.

9.4 If the Purchaser is involved in insolvency procedure, also alert or assisted composition, has become insolvent or has, upon its own fault, reduced the guarantees given, or fails to provide the Supplier with the requested guarantees, the Supplier may

demand payment immediately, regardless of whether the agreed payment period was in favour of the Purchaser, pursuant to art. 1186 civil code.

9.5 The non-payment or delay of payment for more than 8 working days, of even a single supply, shall lead to termination of the contract pursuant to art. 1456 civil code. In any case, all delayed payments shall be subject to default interest, charged in accordance with legislative decree 231/02, plus compensation for greater losses and any costs incurred by the Supplier.

10) Reservation of title

10.1 In case of instalments payment and/or deferred payment, until full and final settlement of the invoice, the Products supplied shall be considered property of the Supplier pursuant to art. 1523 civil code. The risks will be borne by the Purchaser since the delivery.

10.2 In case of delayed payment of a single instalment, the Supplier may demand the termination of the contract and any sum already collected by the Supplier shall be retained by the latter as an indemnity for the use of the Products, pursuant to art. 1526, co. 2 civil code. The supplier shall be entitled to take action for any cost incurred to recover possession of the products, and for any loss resulting from damage to the same.

11) Complaints and warranty

11.1 Any complaints regarding the quantity or integrity of the packages or products must be reported directly to the carrier at the time of delivery, by marking the waybill or delivery note with the words "provisionally accepted".

11.2 Any defects in the Products delivered must be reported to the Supplier in writing, by registered post or certified email, within eight days from the date of delivery. The unverifiable defects at time of delivery must be reported to the Supplier in writing, by registered post or certified email, within eight days from the date of their discovery and, in any case, within one year from the date of the delivery.

11.3 Any difference in the quantity of goods delivered compared to the order shall not entitle the Purchaser to terminate the contract nor to suspend the payments, but only to the completion of the consignment with the missing goods.

11.4 The Purchaser shall not use any defective products.

11.5 The Supplier's warranty is granted for 12 months from the date of delivery for Products in normal conditions of conservation, and after defects have been reported, in accordance with the procedure indicated in paragraph 11.2 above. The warranty only concerns the defects that make the products unsuitable for the use they're intended for or the defects that appreciably decrease the value of the products.

11.6 The warranty shall not cover any defects or damage deriving from normal use, any accident not attributable to Supplier, any

changes made by a person other than the Supplier, incorrect use, storage or treatment of the Products.

12) Return goods

12.1 Except in exceptional circumstances with prior written approval, the Supplier doesn't accept return goods. Every return must be preceded by a written claim from the Purchaser and it must be previously authorized in written by the Supplier.

12.2 The shipping charges shall be covered by the Purchaser.

12.3 In case of return, the Supplier reserves the right to examine the return goods to verify the applicability of the warranty referred to the point 11); if the warranty isn't applicable, the return goods will be returned to the Purchaser and the shipping charges shall be covered by the latter.

13) Assignment of contract

The Purchaser may not assign this Agreement or any individual supplies to any third party, without the written authorization of the Supplier.

14) Termination

14.1 Either Party may terminate this Agreement by giving three months' advance notice in written by registered letter or certified email, without prejudice to the validity of this agreement for the already made orders.

14.2 The Supplier may withdraw, without notice, in the case of: commencement of actions or proceedings for the liquidation of the Supplier; - interruption or suspension of the Supplier's production operations; - the Supplier is subjected to insolvency procedure; - the Supplier has declared in writing that it cannot meet its obligations according to the terms of the Agreement or of the individual orders.

15) Termination clause

Pursuant to art. 1456 civil code, the Supplier may withdraw from the contract with written notice in the event of: - failure to comply with the terms of delivery referred to the point 6.4 ; - non-payment or delayed payment referred to the point 9.5; - the commencement of the Purchaser liquidation proceedings; - interruption or suspension of the Purchaser's production operations; - if the conditions referred to the point 9.4 occur; - in any case of serious breach of contract by the Purchaser.

16) Communications

All the communications between the Parties will be valid if they reach the stated addresses.

17) Governing law

For all matters not expressly agreed herein, this Agreement shall be governed by, and construed in accordance with, the law of Italy, with the express exclusion of the provisions of the 1980 Vienna Convention on the international sale of goods.

18) Jurisdiction

Except in cases where the jurisdiction of a different court is provided by law, the Parties submit all their disputes arising out of or in connection with this Agreement to the exclusive jurisdiction of the Courts of Vicenza.

19) Privacy

The Supplier shall process the Purchaser's data electronically and/or manually, in accordance with the principles of legality and fairness and in accordance with legislative decree 196/2003 and of the EU / 2016/679 regulation.

Personal data may be used directly by The Supplier or through trusted service providers (banks, credit institutions, insurance companies, administration and/or IT services providers, debt recovery agencies), in their capacity as data controller or data coordinator but only to comply with the legal obligations including fiscal and accounting obligations and the contractual obligations. In consideration of the existence of electronic computer links or electronic correspondence with the above parties, the data may be transferred abroad.

Without prejudice to the right of the Purchaser to exercise the access right to personal data under art. 15 of the 2016/679 EU regulation and the rights provided for by articles 16, 17, 18, 21 of EU Regulation 2016/679 regarding rectification, cancellation, portability, limitation to treatment and the right to object, in the manner established by art. 12 of the 2016/679 EU Regulation.

Declaration pursuant to and for the purposes of art. 1341 of the Civil Code: the Purchaser declares to approve specifically the following conditions: 2.2) changes and variations; 3) object; 5.2) restricted liability during demonstration; 6) delivery; 9) delayed payment or non-payment; 10) reservation of title; 11) complaints and warranty; 12) return goods; 13) assignment of contract; 14) termination; 18) jurisdiction.

CONTACTS

Via dei Carabinieri, 44/45
36040 Torri di Quartesolo (VI)
ITALY

+39 0444 583599

info@mixersrl.com



For more information visit our website:

www.mixersrl.com

Follow us on:



DISTRIBUTED DIRECTLY BY OUR DEALERS

In order to improve our product range we reserve the right to change features and prices without prior notice. Non-contractual document. Non-contractual text and photos. Content subject to typographical errors.

www.mixersrl.com